


Pigtail Photodetector Module



Performance Characteristics

- ◆ High responsivity, low return loss
- ◆ Low dark current, low capacitance
- ◆ Planar incident structure
- ◆ High reliability and long operation life

Applications

- ◆ Analog Optical Receiver
- ◆ CATV & CDMA
- ◆ Test Equipment

Optical and Electrical Characteristics(T=25°C)

Parameter	Symbol	Unit	Min	Typ	Max	Test Condition
Operating Wavelength	λ	nm	1100		1650	-
Dark Current	I_d	nA			1	$V_r = -5V$ 25°C
Responsivity	R	A/W		0.87		$V_r = -5V$ $\lambda = 1310nm$
				0.95		$V_r = -5V$ $\lambda = 1550nm$
Active Diameter	Φ	μm		55		-
Rise time/Fall time	t_r/t_f	ns		0.1		$RL = 50\Omega$
Capacitance	C	pF		0.46	0.65	$V_r = -5V$
Composite Second Order Beat	IMD2	dBc	-75			
Composite Third Order Beat	IMD3	dBc	-85			
Optical Return Loss		dBm	-40			

■ Absolute Maximum Ratings($T_c=25^{\circ}\text{C}$)

Parameter	Symbol	Unit	Min	Max
Saturation	Ps	mW		5
Forward current	If	mA	-	10
Reverse voltage	Vr	V		30
Reverse current	Ir	mA		5
Operating Temperature	Top	$^{\circ}\text{C}$		-40~+85
Storage temperature	Tstg	$^{\circ}\text{C}$		-40~+85

■ Dimension




Fig2. Pigtail Module

■ Order Information

WSPDM-X-XX-X-XX-X-XX

X	XX	X	XX	X	XX
Module Type	Active area	Connector	Wavelength	Reverse Voltage	Others
2:Pigtail	01:50um	1:SC/PC	00: All wavelength	0:0V	
	02:60um	2:SC/APC		5:5V	
	03:70um	3:FC/PC	15: 1550nm		
	04:75um	FC/APC			
	05:80um				
	06:300um				

Such as WSPDM-1-03-2-00-P-5:WS:WSEE, PDM: Single PIN module 2: Pigtail 03:70um

2:SC/APC 00: All wavelength 5:5V

■ Package Dimension



Note: The specific packing box size is determined according to the quantity ordered by the customer.

 **SHANDONG WANSHUO OPTOELECTRONICEQUIPMENT CO.,LTD**

Add: 7th Floor, Block C, Torch Venture Plaza, No. 111 Liuquan Road, Zibo City, Shandong

Province, China

Post code: 255086

Tel: 0533-3599957

Fax: 0533-3599955

E-mail: admin@wanshuo.net

Web: www.wanshuo.net